

CTCP Plate

ECOO-CTCP-ES



EcooGraphix

Model	ECOO-CTCP-ES
Plate Type	Positive CTCP Plate
Application	High grade commercial and newspaper printing
Substrate	Electro chemically Grained and Anodized lithographic Aluminum
Coating	Single-layer system ,IR sensitive, positive acting
Gauge	0.15, 0.30 (mm)
Maximum short grain width	Maximum width 1280mm
Length of run	Unbaked: 80,000 to 100,000 impressions Baked: Over 100,000 impressions
Plate setters	Major brands of CTCP platesetters
Exposure energy	50-70 mj/cm ²
Spectral Sensitivity	400-430 nm - UV Laser
Resolution	2-99% at 200 LPI
Photosensitive Wave Length	405nm
Image color	Blue
Processor	Major brands of processors
Developer	EcooGraphix or other major brand developer
Processing temperature	23°C +/- 2°C
Developing time	25-30 sec
Processing Speed	0.80-1.20 m/min
Safelight	Handle under yellow safelight (UV free)
Shelf life	12 months under recommended storage conditions
Packaging	Available in all standard formats, including bulk packaging options, such as APL packaging
Storage and handling	Stored in a cool and dry environment, away from excessive cold, heat and humidity



Hangzhou EcooGraphix Digital Technology Co, Ltd.

Add: Room 708, Tianheng Building, No.1509 Binsheng Rd, Binjiang District, Hangzhou, China

Tel: 0086 571-87391001 Fax:0086 0571-81391066

E-mail:info@ecoographix.com Website: www.ecoographix.com