Technical Specification of Ink ECOO-IN-F



Туре	ECOO-IN-F					
	Printing speed: 8,000rph-10,000rph					
	Environment friendly					
Features	Good water/ink balance					
	Rich in printing layer					
	Clear and complete in printing dots					
	Quick-drying performance, quick setting, quick turn					
Packing	1 or 2.5 kg/tin					
Shelf Life	3 years(from the production date); product against light and humidity					
	ECOO-IN-F printing ink is suitable for printing packaging, advertisement, label, brochures and					
Application	decorating products on art paper, coated paper, offset paper, cardboard, etc., especially suitable for					
	single-color and multi-color printing.					

ITEM/TYPE	TACK VALUE	FLUIDITY (mm)	PARTICLE SIZE (μm)	SETTING TIME (min)	DRYING TIME (hr)	SKINNING TIME (hr)		
F	6-7	35±1	15	4	< 10	>15		
YELLOW								
F	5.5-6.5	34±1	15	4	< 10	>15		
MAGENTA								
F	6.5-7.5	35±1	15	4	< 10	>15		
CYAN								
F	7-8	35±1	15	4	< 10	>15		
BLACK								
Tack Value	The value is measured in 1 minute by inkometer at 32 $^\circ\!{ m C}$ and 400rpm.							
Set Time	Printing adapter, 157g art paper, the volume of ink-coating can be up to 0.125cc							
Condition of test	Room temperature 25 $^\circ \!\! \mathbb{C}$, humidity 65%-75%							

ITEM/TYPE	Light Resistance	Heat Resistance	Acid Resistance	Alkaline Resistance	Alcohol Resistance	Soap Resistance			
F	4	5	5	4	4	4			
YELLOW									
F	3	5	5	5	4	5			
MAGENTA									
F	7	5	5	5	5	5			
CYAN									
F	7	5	5	5	5	5			
BLACK									
Light Fastness	1-8 (weak-strong)								
Others	1-5 (weak-strong)								

Hangzhou EcooGraphix Digital Technology Co, Ltd.

Add: Room 708, Tianheng Building, No.1509 Binsheng Rd, Binjiang District, Hangzhou, China Tel: 0086 0571-87391001 Fax: 0086 0571-81391066 E-mail: info@ecoographix.com Website: www.ecoographix.com